CAPRICCIO SOL LED

Architectural Outdoor










FEATURES

- · ADA Compliant
- Aluminum Fascia and Mount Pan w/ Matte Silver Powder Coat Finish
- · CSA Listed Wet Location For Wall Mount Only
- Drivers are Constant Current Dimmable 0-10V
- LED Light Fixture
- Mounts Directly to Flat Surface w/ Wall Anchors (By Others)
- · Open Top and Bottom
- · Self-Contained Waterproof LED Module Assembly
- · UL Class 2 Driver









FINISHES

Antique

Copper

Textured Black



Textured **Bronze**



Textured White







For RAL Colors & Custom Match -Contact Teron Lighting Inc.





CAPRICCIO SOL LED

Architectural Outdoor



F	ix	t	u	r	e	C	0	re
---	----	---	---	---	---	---	---	----

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
CPO - Capriccio	L20.0-ZE700 - 20W @ 700mA 0-10V Dimming Driver	120 - 277V (50/60Hz)	0-10V Dimming
ORDER INFO			
СРО	L20.0-ZE700	120 - 277V	Not Applicable

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
SOL	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel TB - Textured Black BZ - Textured Bronze TW - Textured White	30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	F - Fused SPD – Surge Protection Device
ORDER INFO			
SOL	AC	30K	F

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS				
CPO	L20.0	• 30K SPECS • 30K - 3000K Color Temp • 2000 LED Source Lumens • 100 LED Source Lumens Per Watt				
			CPO L20.0 •30K - 3000K Color Temp •2000 LED Source Lumens •100 LED Source	CPO	CPO	CPO

REPLACEMENT PART	PART NO	NOTES
N/A	N/A	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004



