CORNERSTONE W UDL LED

Architectural Outdoor



-		-	-
			-

TYPE: PO#: COMMENTS:


PROJECT:

QTY:

FEATURES

- Up And Down Light
- Clear Tempered Glass Diffusers
- Constant Voltage Modules (Excluding L42.0)
- CSA Listed Wet Location
- Die-Cast Aluminum Housing w/ Textured Black Polyester Powder Coat Finish
- Emergency Battery Available (Excluding L64.0)
- LED Light Fixture
- Mounts Direct to Flat Surface w/ Two #8 Wall Anchors (Not Included)
- Surge Protector
- Thermal Compensation Technology Ensures Longer LED Lifetime Ideal For Fixtures Being Placed in Area w/ Fluctuating or Higher Ambient Temperatures

LINE DRAWING







TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

CORNERSTONE W UDL LED

Architectural Outdoor

SP

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
CRNW-UDL - Cornerstone W Up and Down Light	L32.0-12CV - 32W @ 12V Constant Voltage Non-Dimming L42.0-ZE1100 - 42W @	120 - 277V	Not Applicable (Dimmable 0-10V)
ORDER INFO	1100mA Constant Current 0-10V Dimming Driver		
		100 0751	
CRNW-UDL	L32.0-12CV	120 - 277V	Not Applicable

Aesthetics & Options

TRIM		FINISH		CC	LOR TEMP		OPTIONS	
Not Applicable		AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel	er Black (Standard) BZ - Textured Bronze TW - Textured		30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp		EB - Integral EM Battery (Excluding L64.0) DH - Deep Housing PCL - Photocell	
ORDER INFO								
Not Applicab	le	AC		30	<		EB	
		anufacturable product)						
PROD	SOURCE	30K SPECS						
CRNW-UDL	L32.0-12CV L42.0	 30K - 3000K Color Temp 2570 Total LED Source Lumens 102.8 Total LED Source Lumens Per Watt 2528 Total Delivered LED Lumens 79.0 Total Delivered LED Lumens Per Watt 3276 Total LED Source Lumens 78 Total LED Source Lumens Per Watt 2956 Total Delivered LED Lumens 70.4 Total Delivered Lumens Per Watt 						

REPLACEMENT PART	PART NO	NOTES
Black Glass Lens	3702824	
Clear Glass Lens	37028	Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

CORNERSTONE W UDL LED

Architectural Outdoor

LED (SP)

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core				
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
CRNW-UDL - Cornerstone W Up and Down Light	L56.0-ZE12CV - 56W @ 12V Constant Voltage 0-10V Dimming Driver L64.0-12CV - 64W @ 12V Constant Voltage Non-Dimming Driver	120 - 277V	(Dimmable 0-10V) Not Applicable	
ORDER INFO	2			
CRNW-UDL	L56.0-ZE12CV	120 - 277V	0-10V	

Aesthetics & Options

TRIM		FINISH	FINISH		COLOR TEMP			OPTIONS		
Not Applicable		AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel	ue Copper TB - Textured Black (Standard) ze Mist BZ - Textured Bronze TW - Textured		30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp			EB - Integral EM Battery (Excluding L64.0) DH - Deep Housing PCL - Photocell		
ORDER INFO										
Not Applicab	le	AC		30K			EB			
		nanufacturable product)								
PROD	SOURCE	30K SPECS								
CRNW-UDL	L56.0 L64.0	 30K - 3000K Color Temp 4424 Total LED Source Lumens 79.0 Total LED Source Lumens Per Watt 4057 Total Delivered LED Lumens 72.4 Total Delivered Lumens Per Watt 5056 Total LED Source Lumens 102.1 Total LED Source Lumens Per Watt 4796 Total Delivered LED Lumens 74.9 Total Delivered LED Lumens Per Watt 								

REPLACEMENT PART	PART NO	NOTES
Black Glass Lens	3702824	
Clear Glass Lens	37028	Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.