CYPRESS 1T XL MCT LED

Architectural Indoor

CUL US LISTED	LED
------------------	-----



FEATURES

- 0-10V Dimmable
- · Direct Down Light
- Frosted Acrylic Lens
- LED Light Fixture
- Low Profile Seamless Aluminum Frame
- MCT 3000k, 3500k, 4000k
- Rectangular Driver Box Hanging System (Standard)


PROJECT: TYPE: PO#:

COMMENTS:

- Suspended LED Rectangle Dimensions: 40" x 20"
- Suspended LED Rectangle Height: 2.75"
- Suspended LED Rectangle Thickness: 0.49"
- Suspension Cables are 6' Long and Field Adjustable
- UL Listed Dry Location For Ceiling Mount

LINE DRAWING

QTY:







TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

CYPRESS 1T XL MCT LED

Architectural Indoor

PROJECT: TYPE: PO#: QTY: COMMENTS:

Fixture Core				
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
CYR1T-XL - Cypress 1 Tier 40" x 20" L50.0-ZE1025mA - 50.0W @ 1025mA Dimming Driver		120V - 277V	ZE - 0-10V Dimming	
ORDER INFO				
CYR1T-XL	L50.0-ZE1025	120-277V	Not Applicable	

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	
Not Applicable	BK - Matte Black MW - Matte White (Standard) PL - Platinum	MCT - 3000K, 3500K, 4000K Color Temp.	
ORDER INFO			

PROD	SOURCE	30K SPECS	40K SPECS	_	-	
CYR1T-XL	L50.0	• 30K - 3000K Color Temp • 4050 LED Source Lumens • 81 Lumens Per Watt • 80 CRI	 40K - 4000K Color Temp 4150 LED Source Lumens 83 Lumens Per Watt 80 CRI 			
				1	1	1

REPLACEMENT PART

NOTES



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM