LYNX SQUARE 23.6" LED

Architectural Indoor

E	(II)	LED
U -	LISTER	_

ROJECT:	
YPE:	
O#:	QTY:
OMMENTS:	




FEATURES

- Acrylic Lens
- Aluminum Construction
- ADA Compliant
- Ceiling or Wall Mounted
- CRI ≥ 90
- Dimmable @ 120V
- Dimmable to 10%
- ETL Listed For Dry Locations
- LED Light Fixture
- 120V
- ~50,000 Hour Rated LED Life

LINE DRAWING

INF DRAWING NOT TO SCALE



FINISHES

Satin Dark Gray



LYNX SQUARE 23.6" LED

Architectural Indoor

失 (19) 년

失 🖤 😐

Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	·

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
LXS23.6 - Lynx Square 13.6" LED	L62.0-LT2100 - 62W @ 2100mA ELV Low Voltage 2-Wire Dimming Electronic Driver (Leading or Trailing Edge)	120V	ELV or TRIAC Dimming @ 120V
ORDER INFO			
LXS23.6	L62.0-LT2100	120V	ELV, TRIAC

Example ^

Aesthetics & Ontions

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	SDG - Satin Dark Gray	30K - 3000K Color Temp	Not Applicable
RDER INFO			
Not Applicable	SDG	30K	Not Applicable

PRO	D SOURCE	30K SPECS		
PRO LXS23		30K SPECS • 30K - 3000K Color Temp • 5040 LED Source Lumens • 81.3 LED Source Lumens Per Watt		

MATES	

Don't see the configuration you are looking for? Call us today at (513) 858-6004

