

# SPIRIT PANEL 2X4 LED

Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

## FEATURES

- 0-10V Dimmable (10%-100%)
- 120 Degree Beam Angle
- 5 Year Warranty
- Aluminum Frame In White Finish, Steel Die-Formed Back Enclosure
- cULus Listed Damp Location For Ceiling Mount
- IC Rated For Insulated Ceilings
- Integral Earthquake Clips for Secure Attachment
- LED Backlit Flat Panel
- DesignLights Consortium® (DLC) Premium Listed
- Linear Driver Integrated Into Side of Panel
- Operating Temp Range -20 Degrees C to 35 Degrees C
- PMMA Lenses Over LEDs, PS Diffuser
- Integral Battery Available
- RoHS, FCC
- Surface Mount and Suspension Mount Cable Kit Accessories Available
- Weight: 8.82 lbs

## LINE DRAWING

LINE DRAWING NOT TO SCALE



## FINISHES

Matte White



# SPIRIT PANEL 2X4 LED

Architectural Indoor



Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	TRIM	SOURCE/WATTAGE	VOLTAGE
FPE2X4-P - Flat Panel 2' x 4'	Not Applicable	L40.0 L50.0	UNV (120V - 277V)
ORDER INFO			
FPE2X4 Example ^	Not Applicable	L40.0	UNV

Aesthetics & Options

DIM	FINISH	COLOR TEMP	OPTIONS
ZE (0-10V Dimming)	MW - Matte White (Standard)	835K - 80 CRI 3500K Color Temp. 840K - 80 CRI 4000K Color Temp. 850K - 80 CRI 5000K Color Temp.	2CA - Two Cable Suspension Mounting Kit (See Install Instructions) 4CA - Four Cable Suspension Mounting Kit (See Install Instructions) EB - Integral Emergency Battery REC - Recessed Flange Kit SRK - Surface Mounting Kit (See Install Instructions)
ORDER INFO			
ZE Example ^	MW	835K	2CA

Actual production units may vary from the values reported here by up to +/-10%

## PERFORMANCE (DELIVERED LUMENS)

WATTAGE	80 CRI 3500K	LUMENS/WATT	80 CRI 4000K	LUMENS/WATT	80CRI 5000K	LUMENS/WATT
L40.0	5000	125	5100	128	5200	130
L50.0	6250	125	6375	128	6500	130

## ELECTRICAL DATA

WATTAGE	120V	208V	240V	277V	347V	480V
L40.0	0.33A	0.19A	0.17A	0.14A	N/A	N/A
L50.0	0.42A	0.24A	0.21A	0.18A	N/A	N/A

REPLACEMENT PART	PART NO	NOTES



TERONLIGHTING.COM  
 33 DONALD DR, FAIRFIELD, OH 45014  
 P: 513.858.6004 F: 513.858.6038  
 E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.