



# RHL4-ICAT

## 4" IC Air-tight New Construction LED Housing

**PROJECT:** \_\_\_\_\_



**MODEL #:** \_\_\_\_\_

**LOCATION:** \_\_\_\_\_

**CONTACT:** \_\_\_\_\_



### DIMENSIONS



#### USE OF PRODUCT

The RHL4-ICAT is the ideal product for general purpose recessed LED housing for residential, commercial, hospitality, health care, restaurant and retail applications.

#### CONSTRUCTION

- Minimum Clearance Rated for IC/ Non - IC application. "IC" or insulated ceiling housings are rated for direct contact with insulation. No minimum clearance is required.
- Ceiling Thickness Up to 1 1/4.
- Bar Hangers Bar Hangers are adjustable from 13-5/8 to 25" and can be repositioned to 90° on plaster frame. Pre-installed "real nail" easily installs in regular lumber, engineered lumber
- Junction Box Junction box is listed for through branch circuit wiring and contains seven 7/8" knockouts and four ROMEX pryouts with Romex cable clamp. Ground wire provided on J-Box.
- New Construction Frame Galvanized steel construction.
- Connection Quick connect provided for easy connection to REC Series LED module to meet non-screw base socket requirements per California Title 24.

#### LABELS/COMPLIANCE

cUL listed  
 Certified under ASTM-283 for Air-Tight Construction  
 Title 24 Compliant

4" IC Air-Tight New Construction LED Housing



### ORDERING INFO

**RHL4-ICAT**

Series

RHL4-ICAT - 4" IC Air-Tight New Construction LED Housing



www.rayonlighting.com  
 info@rayonlighting.com

tel: 323.446.2626  
 fax: 323.446.2606

Specification and product availability  
 subject to change without notice