






#### 21w LED 1791 Lumens

IP66 • Suitable For Wet Locations IK08 • Impact Resistant (Vandal Resistant) Weight 4.8 lbs







**Mounting Detail** 

### Construction

#### Aluminum

Less than 0.1% copper content – Marine Grade 6060 extruded & LM6 Aluminum High Pressure die casting provides excellent mechanical strength , clean detailed product lines and excellent heat dissipation.

#### Pre paint

8 step degrease and phosphate process that includes deoxidizing and etching as well as a zinc and nickel phosphate process before product painting.

#### Memory Retentive -Silicon Gasket

Provided with special injection molded "fit for purpose" long life high temperature memory retentive silicon gaskets. Maintains the gaskets exact profile and seal over years of use and compression.

#### Thermal management

I M6 Aluminum is used for its excellent mechanical strength and thermal dissipation properties in low and high ambient temperatures. The superior thermal heat sink design by Ligman used in conjunction with the driver, controls thermals below critical temperature range to ensure maximum luminous flux output, as well as providing long LED service life and ensuring less than 10% lumen depreciation at 50,000 hours.

<u>Surge Suppression</u> Standard 10kv surge suppressor provided with all fixtures.

# BUG Rating B5 - U5 - G5

All Ligman products go through an extensive finishing process that includes fettling to improve paint adherence.

UV Stabilized 4.9Mil thick powder coat paint and baked at 200 Deg C. This process ensures that Ligman products can Deg C. This process ensures that Ligman products ca withstand harsh environments. Rated for use in natatoriums.

The Inspired by nature Finishing is a unique system of decorative powder coating. Our metal decoration process can easily transform the appearance of metal or aluminum product into a wood grain finish

This patented technology enables the simulation of wood grain, and even marble or granite finish through the use of decorative

The wood grain finish is so realistic that it's almost undistinguishable from real wood, even from a close visual inspection. The system of coating permeates the entire thickness of the coat and as a result, the coating cannot be removed by normal rubbing, chipping, or scratching.

<u>The Coating Process</u>
After pre-treatment the prepared parts are powder coated with a specially formulated polyurethane powder. This powder provides protection against wear, abrasion, impact and corrosion and acts as the relief base color for the finalized metal

The component is then wrapped with a sheet of non-porous film with the selected decoration pattern printed on it using special high temperature inks.

This printed film transfer is vacuum-sealed to the surface for a complete thermo print and then transferred into a customized oven. The oven transforms the ink into different forms within the paint layer before it becomes solid. Finally, the film is removed, and a vivid timber look on aluminum remains

Wood grain coating can create beautiful wood-looking products of any sort. There are over 300 combinations of designs currently in use. Wood grains can be made with different colors, designs, etc.

Our powder coatings are certified for indoor and outdoor applications and are backed by a comprehensive warranty. These coatings rise to the highest conceivable standard of performance excellence and design innovation.

#### Added Renefits

- Resistance to salt-acid room, accelerated aging Boiling water, lime and condensed water resistant
- Anti-Graffiti, Anti-Slip, Anti-Microbial, Anti-Scratch Super durable (UV resistant)
- TGIC free (non-toxic)

#### Hardware

Provided Hardware is Marine grade 316 Stainless steel.

### **Anti Seize Screw Holes**

Tapped holes are infused with a special anti seize compound designed to prevent seizure of threaded connections, due to electrolysis from heat, corrosive atmospheres and moisture.

### Crystal Clear Low Iron Glass Lens

Provided with tempered, impact resistant crystal clear low iron glass ensuring no green glass tinge.

### Optics & LED

Precise optic design provides exceptional light control and precise distribution of light. LED CRI > 80

### Lumen - Maintenance Life

L80 /B10 at 50,000 hours (This means that at least 90% of the LED still achieve 80% of their original flux)

Square surface architectural floodlight range. Four sizes of square artistic precision with wide range of beam distributions.

A range of square outdoor IP66 floodlight projectors that meets both aesthetic and functional applications. This cubic floodlight range is available with 4 different sizes, starting with a small 2.4" square profile at 3w, and increases proportionately to 3" at 11w, 4.5" at 21w and 5.5" square at 40w. This glare free luminaire is available in Narrow 10° beam, Medium 19°, Wide 33°, Very Wide 71° and Elliptical 41°x14° beam patterns.


This luminaire is engineered to meet harsh outdoor environments, as well as being able to be used as a decorative indoor product. The Lador is provided with an integral driver and has accessories that include; dichroic color filters, linear spread lens, honeycomb louvres and anti-glare visors.

This floodlight also has a unique aiming and locking system for precise mounting and beam aiming.

The Lador product family consists of; floodlights, wall sconces, ceiling mounted squares and cluster column event poles.

This luminaire is available with a natatorium rated coating.

### Additional Options (Consult Factory For Pricing)







Linear Spread

A52021 **H**oneycomb

Large Ground

Anti Glare Viso







**Dichroic Color Filters** 

A50181

A50281 24" Arm Threaded



# **ULD-50021**

Lador 3 Floodlight



**PROJECT** DATE **QUANTITY** NOTE **TYPE** 

#### ORDERING EXAMPLE || ULD-50021-21w LED - N - W30 - 02 - 120/277v ULD-50021 **LAMP BEAM LED COLOR FINISH COLOR VOLTAGE** 21w LED N - Narrow 10° W27 - 2700K 01 - BLACK RAL 9011 120/277v Other - Specify 1791lm M - Medium 19 W30 - 3000K 02 - DARK GREY RAL 7043 W - Wide 33° W35 - 3500K 03 - WHITE RAL 9003 VW - Very Wide 71° W40 - 4000K 04 - METALLIC SILVER RAL 9006 E - Elliptical 41° x 14° 05 - MATTE SILVER RAL 9006 06 - LIGMAN BRONZE 07 - CUSTOM RAL INSPIRED BY NATURE FINISHES SW01 - OAK FINISH SW02 - WALNUT FINISH SW03- PINE FINISH DF - DOUGLAS FIR FINISH THERE IS AN ADDITIONAL CW - CHERRY WOOD FINISH COST FOR THESE FINISHES **NW - NATIONAL WALNUT FINISH** SU01 - CONCRETE FINISH SU02 - SOFTSCAPE FINISH

# **ADDITIONAL OPTIONS**

NAT - Natatorium Rated A51314 - Linear Spread Lens

A52021 - Honeycomb Louvre

S20LGS - Large Ground Spike 20"

A53031 - Anti Glare Visor

AMB - Turtle Friendly Amber LED

DIM - 0-10v Dimming

A50181 - Surface Pedestal 24" Extended Arm

A50281 - 1/2" Threaded 24" Extended Arm

**DICHROIC COLOR FILTERS** 

SU03 - STONE FINISH SU04 - CORTEN FINISH

A51316 - Red Color Filter

A51317 - Blue Color Filter

A51318 - Amber Color Filter

A51319 - Green Color Filter

## More Custom Finishes Available Upon Request

Consult factory for pricing and lead times



Pine



Mahogany

















# **Lador Product Family**



Lador 6

Lador 11

• ULD-80021-21w-1975lm

• ULD-30011-11w-904lm





• ULD-50011-11w-904lm





Lador 12







• ULD-50021-21w-1975lm • ULD-50022-18w RGBW-1016lm



Lador 8 • ULD-30031-39w-3568lm



ULD-20011-4x2\w-4x1975Im [13']
 ULD-20021-4x29w-4x3568Im [13']
 ULD-20012-4x21w-4x1975Im [19.6']
 ULD-20012-4x39w-4x3568Im [19.6']
 ULD-20011-4x31w-4x1975Im [26.2']
 ULD-20011-4x39w-4x3568Im [26.2']



• ULD-50081-3w-222lm



• ULD-50031-39w-3568lm • ULD-50032-36w RGBW-1929Im



Lador 9

• ULD-80001-3w-222lm



Lador 5

Lador 10 • ULD-80011-11w-904lm



• ULD-50041-3w-222lm



• ULD-50051-11w-904lm



• ULD-50091-11w-904lm



• ULD-50101-21w-1975lm



Lador 3 TKM

• ULD-50061-21w-1975lm

· ULD-50111-39w-3568lm