DECO® LIGHTING

D470-LED

Client:	Order #:	
Project Name:	Type:	_ Qty:

Medium Traditional Wall Pack

Performance Data

CRI

70+

CCT

4000K, 5000K

Projected Lifetime

50,000 Hours (L70); 50,000 Hours (L80)

Dimming

0-10V Dimming Standard, 100% down to 10%

Operating Temperature

-40°C to +40°C Ambient

ETL Listed

Suitable for dry, damp, wet locations









Description

The D470-LED medium wall pack provides a cost-effective, durable and efficient exterior light source for any application with maximum performance and minimum maintenance. The D470-LED delivers up to 128 lumens per watt of energy-efficient LED performance paired with a traditional design.

Features

- Heavy duty two piece die cast aluminium housing is top hinged for ease of maintenance. Two captive stainless steel door fasteners.
- 1/2" threaded conduit entry with coin plug.
- Weight: 7.7lbs (40W); 8.6lbs (60W)
- Dark bronze polyester powder finish for excellent impact,
- corrosion and UV resistance.
- Clear prismatic borosilicate glass reflector is thermal/shock resistant.
- DLC Premium Listed
- 10-Year Limited Warranty



Ordering Information

A FIXTURE SERIES

D470-L Medium Wall Pack

B WATTAGE/LUMENS

40 40W/4750^{1,2} 60 60W/7280^{1,2}

C CCT

40 4000K 50 5000K

VOLTAGE

U 120-277V

B FINISH

Z Bronze

OPTIONS


T Push Button Photocell


Emergency

¹ Delivered lumens (4000K) - For 5000K multiply by 1.02

² DLC Premium Listed

Dimensions







	Inches
X ₁	14.20
X ₂	9.10
X_3	7.68

Photometrics

Model 60W 4000K





Zonal Lumen Summary

Zone	Lumens	%Luminaire	%Luminaire
0-30	1,490.2	20.5%	20.5%
0-40	2,384.3	32.7%	32.8%
0-60	4,310.5	59.2%	59.2%
60-90	2,258.0	31%	31%
70-100	1,722.5	23.6%	23.7%
90-120	647.9	8.9%	8.9%
0-90	6,568.5	90.2%	90.3%
90-180	708.0	9.7%	9.7%
0-180	7,276.5	99.9%	100%

DLC Premium Listed Models (Utility Rebates)

40W	60W
D470-L4050UBZ	D470-L6050UBZ
D470-L4040UBZ	D470-L6040UBZ