

EDGE EV3WW


3" Recessed Linear Wall Wash

Key Features

- Extruded aluminum trim with formed cold rolled 20 gauge steel back box housing
- Highly reflective, die-formed white, painted steel reflector
- 5-year limited warranty covers LED, driver and fixture
- UL and cUL listed. IC rated
- Approved for dry/damp location unless otherwise noted
- Maximum fixture weight is 15lbs (per 4ft fixture)
- Room-Side Maintenance for LED system
- Designed to be mounted facing wall between 12"-18" from wall
- Buy American Act compliant



Example Part #: EV3WW-830HO-26'-G1-U-OL2-1-0-W



CRI, CCT & OUTPUT ^{QS, 1}	LENGTH ²	MOUNTING ³	VOLTAGE
<p>_27_ - 2700K _30_ - 3000K _35_ - 3500K _40_ - 4000K CL - Custom Lumens CW - Custom Watts Lumen Output pg. 2 Example: 830HO is 8 = 80 CRI; 30 = 3000K; HO = High Output; Blank = Standard Output</p>	<p>_ - Individual Fixture ^{QS} _ - Continuous Row ^{QS} Length and Pattern pg. 2</p>	<p>G1(G) - 1" (15/16") T Bar ^{QS} G9(G) - 9/16" T Bar ^{QS} GB(G) - 9/16" Bevel T Bar GS(G) - Screw Slot T Bar ^{QS} FL(F) - 1/2" Flange ^{QS} NF(N) - Non Flange ^{QS} SF(S) - Spackle Flange ^{QS} Mounting pg. 3</p>	<p>U - Universal ^{QS} (120 thru 277V) 1 - 120V ^{QS} 2 - 277V ^{QS} 3 - 347V Voltage pg. 3</p>

DRIVER	CIRCUITING	BATTERY & EMERGENCY ⁴	FINISH
<p>OL2 - Osram (1%, 0-10v, standard) ^{QS} OL3 - Osram 347v (10%, 0-10v) EE1 - eldoLED ECOdrive (1%, 0-10v) ES1 - eldoLED SOLOdrive (0%, 0-10v) LH1 - Lutron Hi-Lume (1%, EcoSystem) ^{QS} L51 - Lutron 5-Series (5%, EcoSystem) PL2 - Advance Xitanium (1%, 0-10v) ^{QS} PS1 - Advance Xitanium (50%/100%) ND - Non-Dimming ^{QS} Driver pg. 4</p>	<p>1 - Single Circuit ^{QS} M - Multi Circuit E - Emergency ^{QS} (entire fixture) N - Night Light ^{QS} (entire fixture) Circuiting pg. 4</p>	<p>0 - None ^{QS} P - Bodine 10W ^{QS} I - Iota 10W ^{QS} IC - Iota 10W (CEC Listed) E - Emergency Circuit Section N - Night Light Circuit Section L - Life Safety Circuit Section G - Bodine GTD Battery and Emergency pg. 4</p>	<p>W - White ^{QS} S - Metallic Silver BL - Textured Black BR - Bronze GR - Graphite CC - Custom Color Finish pg. 4</p>

FIXTURE OPTIONS	CONTROLS
<p>QS - QuickShip ^{QS} CP - Chicago Plenum ^{QS} MRF - Fixed MR16 Halogen LMRF - Fixed MR16 LED RC - Rotating Crossbar LC - Clear Lens B - Baffle GLR - Internal Fast Blow Fuse ^{QS} Fixture Options pg. 5</p>	<p>Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.</p>

¹For Quickship CRI, CCT & Output see chart on page 5 ² Individual fixtures come in 2', 3', 4', 5', 6', 8' lengths. Continuous row come in 1' increments. ³Specify mounting for continuous length: G1, G9, GS, FL, NF & SF for continuous rows, G1G, G9G, GSG, FLF, NFN & SFS for individual lengths. ⁴Enter quantity for Battery and Emergency, Example 2P.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



CRI, CCT & Output

- Specify either 80 or 90 CRI
- Longer lead-time may apply for 90 CRI. Consult factory
- 80 CRI = R9≥19 and 90 CRI = R9≥61

Custom Output- Lumens OR Wattage

CL _____	Specify CRI, CCT and desired lumens (i.e. CL835700)	Specify lumens between standard offering listed below. Lumens are specified per color temp
CW _____	Specify CRI, CCT and desired wattage (i.e. CW9407)	Specify watts between standard offering listed below

80 CRI

	Color	Output	Watts per foot	Shielding WW Wall Wash	
				Lumens/ft	LPW
830	3000K	Standard	6.0	329	54.6
830HO	3000K	High	10.3	511	49.7
835	3500K	Standard	6.0	343	56.9
835HO	3500K	High	10.3	534	52.0
840	4000K	Standard	6.0	352	58.4
840HO	4000K	High	10.3	548	53.3

90 CRI

927	2700K	Standard	6.0	270	44.8
927HO	2700K	High	10.3	420	40.9
930	3000K	Standard	6.0	304	50.5
930HO	3000K	High	10.3	471	45.8
935	3500K	Standard	6.0	309	51.3
935HO	3500K	High	10.3	481	46.8
940	4000K	Standard	6.0	314	52.1
940HO	4000K	High	10.3	489	47.6

Length

- Individual units cannot be joined, end trims are factory installed and cannot be removed
- Continuous Rows are made up of even and odd length fixtures; designed to fall on-grid











2	3	4	5	6	8	—
Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Indiv. Fixture	Cont. Run Specify nominal overall row length to the 1'
23" (584.2mm)						
	35" (889mm)					
		47" (1193.8mm)				
			59" (1498.6mm)			
				71" (1803.4mm)		
					95" (2413mm)	
						Specify to the 1' >>>

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Mounting

- Individual Units: specify G_G, FLF, SFS, NFN
- Continuous Runs: specify G_, FL, SF, NF
- All individual units cannot be joined, end trims are factory installed and cannot be removed
- Designed to install into acoustical grid and inaccessible ceilings
- Designed to be 12"-18" away from wall for optimal performance
- Grid retention brackets integral to housing and require mechanical attachment
- Each housing contains 4 grid retention brackets
- Tie off fixture to structure with retention wires
- Approved for dry/damp location unless otherwise noted

G1G Individual Unit	G9G	GBG	GSG	FLF	NFN	SFS
G1 Continuous Run or Pattern	G9	GB	GS	FL	NF	SF
1" (15/16") T-Bar Flange to Flange: 3-13/16" (96.8mm)	9/16" T-Bar For tegular tile installations, fixture position will not be flush to the bottom of the tile Flange to Flange: 3-13/16" (96.8mm)	9/16" T-Bar Rail has bevel edge details. For tegular tile installations, fixture position will be flush to the bottom of the tile Flange to Flange: 3-13/16" (96.8mm)	Screw Slot & 9/16" T-Bar For 9/16" installations with tegular tile, fixture position will be flush to the bottom of the tile Flange to Flange: 3-13/16" (96.8mm)	Exposed Standard 1/2" Flange Detail Flange to Flange: 4-1/8" (104.7mm)	Metal Pan or Millwork Flange to Flange: 3-7/16" (87.3mm)	Drywall, Flangeless Detail Flange to Flange: 5" (127mm)
						
Standard Tile	Standard Tile	Tegular Tile	Tegular Tile			
						
Tegular Tile	Tegular Tile		Tegular Tile			

Voltage

- Some EV3WW configurations will not accommodate all voltage options; consult with factory

U	Universal
1	120 volt
2	277 volt
3	347 volt

Driver

- Standard Driver Option = OL2
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- For more driver options see Pinnacle Resource Guide
- Some EV3WW configurations will not accommodate all driver options; consult with factory

OL2	Osram Optotronic 1%, 0-10v, nominal 1% dimming range
OL3	Osram Optotronic 347v 10%, 0-10v, requires 347v option
EE1	eldoLED ECOdrive 1%, 0-10v Logarithmic
EE2	eldoLED ECOdrive 1%, 0-10v Linear
ES1	eldoLED SOLOdrive 0%, 0-10v Logarithmic
ES2	eldoLED SOLOdrive 0%, 0-10v Linear
LH1	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
L51	Lutron 5-Series 5%, EcoSystem, LDE5
PL2	Advance Xitanium 1%, 0-10v
PS1	Advance Xitanium Step Dimming 50%/100%
ND	Non-Dimming



How to specify Circuiting, Battery and Emergency

- 1**
- Select fixture circuiting from options below
 - Some EV3WW configurations will not accommodate all circuiting options, consult with factory

Circuiting

1	Single Circuit
M	Multi Circuit
E	Emergency Circuit only
N	Night Light Circuit only

- 2** + **3**
- Battery and emergency section options are available in addition to fixture circuit
 - Select battery and emergency section options below; factory shop drawing required
 - Some EV3WW configurations will not accommodate all circuiting options, consult with factory

Battery and/or Emergency *If Required*

- 0** No battery or specific emergency section required

Battery

- Select battery section type if required, indicate total QTY. *Example 2P*
- 90 minute battery runtime; test button is remote
- No battery option available for 2' lengths
- Entire fixture is on battery for lengths up to 5'
- Half of fixture is on battery for 6', 8' housing lengths
- For more battery options available, see Pinnacle Resource Guide

For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 92.3 (LPW) x 10 (watts) = 923 battery lumen output

0	No battery
_P	Bodine 10w Integral
_I	Iota 10w Integral
_IC	Iota 10w Integral <i>CEC Listed</i>

Emergency

- Select emergency section type if required, indicate total QTY. *Example 1E*
- Combine battery and emergency section ordering codes if both options are selected

_E	Emergency circuit section
_N	Night Light circuit section
_L	Life Safety circuit section NO THROUGH WIRE
_G	Bodine GTD, Generator Transfer Device section

Battery OR Emergency Ordering Examples

- Single circuit, 10w Integral Battery Ordering Code: 1-1P
- Emergency only, 10w Integral Battery Ordering Code: E-1P
- Single circuit, GTD required Ordering Code: 1-1G

Combination Section Ordering Examples

- Single circuit, (1) 10w battery, (1) emergency section Ordering Code: 1-1P1E
- Multi circuit, (2) 10w battery, (2) emergency sections Ordering Code: M-2P2E
- Single circuit, (1) night light section Ordering Code: 1-1N

Finish

- Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes
- Selecting a fixture finish other than white may impact lumen output; consult factory for more information

W	White
S	Metallic Silver
BL	Textured Black
GR	Graphite
BR	Bronze
CC	Custom Color

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

EV3WW_LED_SPEC_NOV2020



Fixture Options

- Additional options to enhance the fixture and finish of the product
- Consult factory for MR16 configurations

QS	Quick Ship
CP	Chicago Plenum
MRF	Fixed MR16 Halogen
LMRF	Fixed MR16 LED
RC	Rotating Crossbar
LC	Clear Lens
B	Baffle
GLR	Internal Fast Blow Fuse

Quick Ship

	Output	Mounting	Voltage	Driver	Circuiting	Battery	Finish	Options
10-Day								
EV3WW	80 CRI, all color temperatures, all lumen packages <i>See pg 4</i>	G1(G) 1" T-Bar G9(G) 9/16" T-Bar GS(G) Screw Slot FL(F) 1/2" Flange NF(N) Flangeless SF(S) Spackle Flange	U Universal (120-277) 1 120V 2 277V	OL2 Osram 0-10v, 1% PL2 Advance Xitanium 0-10v, 1% LH1 Lutron LDE1	1 Single Circuit E Emergency N Night Light	1P Bodine 10w Integral Iota 10w 1I Integral	W White	CP Chicago Plenum GLR Internal Fast Blow Fuse

All lengths and continuous rows up to 1,000 ft OR 150 individual fixtures. Consult factory for larger projects.


Controls

- Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information

Photometrics

Wall Wash

Test #	ITL82933
Catalog #	EV3WW-840-4
Lumens	1406 lm
Watts	24.1 W
Efficacy	58 LPW



Candela Distribution

Vert Angle	Horizontal Angle				
	0	22.5	45	67.5	90
0	566	566	566	566	566
5	793	731	567	434	371
10	996	891	563	301	230
15	1038	999	554	210	140
20	903	1016	541	144	88
25	709	926	523	96	69
30	581	765	503	73	57
35	470	611	476	61	48
40	411	509	446	50	39
45	373	408	412	41	29
50	342	351	376	33	11
55	316	310	336	24	4
60	287	275	292	7	3
65	252	243	248	3	1
70	214	208	204	2	1
75	173	167	157	1	0
80	146	124	106	1	0
85	122	96	41	0	0
90	95	70	0	0	0

Luminance Data (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	19888	24775	38132
55	17529	20163	38110
65	15088	17640	38063
75	11620	14192	38811
85	9643	10232	28436

For all available IES files, please visit our website at pinnacle-ltg.com. Photometry testing in accordance to IESNA-LM-79-08 at an NVLAP accredited testing laboratory. Testing conducted at 25°C ambient conditions

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Applications & Certificates

Construction: Formed cold-rolled 20 gauge steel housing. Highly reflective die-formed white painted aluminum reflector.

Shielding: Diffuse snap-in acrylic lens, removable for maintenance.

Mounting: EDGE is designed to install into acoustical grid and inaccessible ceilings. Specify GXG, FLF, SFS, NFN for individual, unjoinable units (individual units will fall on-grid). Specify GX, FL, SF, NF for continuous runs (runs designed to fall on-grid). Consult factory for detailed installation instructions. Maximum fixture weight is 15lbs per 4' fixture.

LED: 25°C test environment. Lumen output/wattage has a margin of +/- 5%; 2' or 3' lengths may have a greater wattage deviation. All luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. Lifetime Projection L70 = 122,900 hours and L90 = 36,600 hours. MacAdam 3-Step Ellipses. Not all products are Lighting Facts listed. For all available IES files, please visit our website at pinnacle-ltg.com.

CRI, CCT & Lumen Output: Two lumen packages available. Standard and High (HO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K, and 4000K. 80 CRI = R9≥19 and 90 CRI = R9≥61.

Voltage: Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify OL3 in Driver section when 347 volt (3) is selected. Some EDGE configurations will not accommodate all voltage options; consult with factory.

Driver: Standard Driver Option is Osram 0-10V, 1% = OL2. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range: -20°F/-30°C to 96°F/35°C. For more driver options, see Pinnacle Resource Guide. Some EDGE configurations will not accommodate all driver options.

Circuiting: Select from single circuit (1), Multi circuit - For multiple circuiting and zone control, requires factory shop drawing (M), Emergency circuit (E), Life Safety (L) or Night

Light circuit (N). For emergency circuiting situations that require no through wire or circuit separation, Life Safety Circuit should be selected. This will provide a separate power feed and only the Life Safety Circuit in that section. Some EDGE configurations will not accommodate all circuiting options; consult with factory.

Battery & Emergency: Select battery or emergency options if required. If battery or emergency option is not required, enter 0. Battery duration is 90 minutes as standard. Test button is remote to fixture. For more Battery options, see Pinnacle Resource Guide.

Finish: Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes or for additional custom color and finish options.

MR16: Ideal for conference rooms, corridors, wall washing, retail spaces and training facilities where accent lighting is required. Fully enclosed compartment eliminates light from entering into our fixture areas. For LED and Halogen lamps (lamps are not included). Consult factory for other lamp types. Standard 60 watt max LED electronic transformer (120v or 277v), 50 watt max halogen lamp transformer (120v or 277v), MR16 installed as an independent circuit. MR16 to match fixture voltage. 277v dimmer must be sourced. Consult factory for MR16 configurations. Pinnacle's MR16 applications are to be used with Soraa lamps with a maximum of 13 transformers on one circuit.

Controls: Specify PD for daylight sensor, requires 0-10v driver. Some EDGE configurations will not accommodate all control options; consult with factory.

Labels: UL and cUL Listed. Standard and HO lumen packages are IC Rated, approved for dry/damp location unless otherwise noted.

Fixture Weight: Maximum fixture weight is 15lbs per 4' fixture.

Buy American Act Compliant

Warranty: EDGE LED offered with a 5-year limited warranty. Covers LED, driver and fixture.