


QIVI™ Q3S-22DI
2' x 2' Direct/Indirect Architectural Shape



Key Features

- 6063-T6 Extruded aluminum housing
- Highly reflective = white painted reflector
- Room side maintenance for LED system
- 5-year limited warranty covers LED, driver and fixture
- UL and cUL listed
- Approved for dry/damp location unless otherwise noted
- Maximum weight is 35.8 lbs.
- Buy American Act compliant



Example Part #: Q3S-22DI-A-HE-830HO-830-AC448G1-U-OL2-1-0-W

Q3S-22DI - DIRECT SHIELDING - INDIRECT SHIELDING - DIRECT OUTPUT - INDIRECT OUTPUT - MOUNTING - VOLTAGE - DRIVER - CIRCUITING - BATTERY & EMERGENCY - FINISH - FIXTURE OPTIONS

DIRECT SHIELDING		INDIRECT SHIELDING		DIRECT CRI, CCT & OUTPUT		INDIRECT CRI, CCT & OUTPUT	
A - Flat Satine Lens HE - High Efficiency Lens HED - Descent Lens <i>Shielding pg. 2</i>		HE - High Output HEA - Ascent <i>Shielding pg. 2</i>		27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K CL - Custom Lumens CW - Custom Watts <i>Lumen Output pg. 2</i> Example: 830HO is 8 = 80 CRI; 30 = 3000K; HO = High Output; Blank = Standard Output		27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K CL - Custom Lumens CW - Custom Watts <i>Lumen Output pg. 2 & 3</i>	
MOUNTING ¹		VOLTAGE		DRIVER		CIRCUITING	
AS4 - 4 AC to Grid, JB, or ST AH4 - 4 AC w/Hub to Grid, JB, or ST <i>Mounting pg. 3</i>		U - Universal (120 thru 277V) 1 - 120V 2 - 277V 3 - 347V <i>Voltage pg. 3</i>		OL2 - Osram (1%, 0-10v, standard) OL3 - Osram 347v (10%, 0-10v) EE1 - eldoLED ECOdrive (1%, 0-10v) ES1 - eldoLED SOLOdrive (0%, 0-10v) LH1 - Lutron Hi-Lume (1%, EcoSystem) L51 - Lutron 5-Series (5%, EcoSystem) PL2 - Advance Xitanium (1%, 0-10v) PS1 - Advance Xitanium (50%/100%) ND - Non-Dimming <i>Driver pg. 3</i>		1 - Single Circuit 2 - Dual Circuit E - Emergency (entire fixture) N - Night Light (entire fixture) <i>Circuiting pg. 4</i>	
BATTERY & EMERGENCY		FINISH		FIXTURE OPTIONS		CONTROLS	
0 - None P - Bodine 10W I - Iota 10W Integral IC - Iota 10W Integral (CEC Listed) <i>Battery and Emergency pg. 4</i>		W - White S - Metallic Silver BL - Textured Black BR - Bronze GR - Graphite CC - Custom Color <i>Finish pg. 4</i>		AM - Antimicrobial Paint GMF - Slow Blow Fuse CC-C - Custom Color Canopy <i>Fixture Options pg. 4</i>		<i>Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.</i>	


¹Example: AS448JB. AS4 = 4 Aircraft Cables, 48 = 48" long cables, JB = connects to junction box. Standard AC cable lengths are 48" and 120", field adjustable.

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.



Direct Shielding

Indirect Shielding



Output

- Specify either 80 or 90 CRI
- Longer lead-time may apply for 90 CRI. Consult factory.
- 80 CRI = R9≥19 and 90 CRI = R9≥61

Custom Output - Lumens OR Wattage

CL _____	Specify CRI, CCT and desired lumens (i.e. CL8351200)	Specify lumens between standard offering listed below. Lumens are specified per color temp
CW _____	Specify CRI, CCT and desired wattage (i.e. CW94015)	Specify watts between standard offering listed below

80 CRI

	Color	Lumens	Shielding		HE		HED	
			A		High Efficiency		Descent	
			Satine		LPW	Watts	LPW	Watts
830	3000K	4000	87.7	45.6	100.0	40.0	80.6	49.6
830HO	3000K	6000	85.2	70.4	97.4	61.6	79.8	75.2
830VHO	3000K	8000	84.7	94.4	97.1	82.4	76.3	104.8
835	3500K	4000	90.9	44.0	102.0	39.2	82.0	48.8
835HO	3500K	6000	88.2	68.0	100.0	60.0	78.9	76.0
835VHO	3500K	8000	87.0	92.0	99.0	80.8	77.5	103.2
840	4000K	4000	92.6	43.2	104.2	38.4	82.0	48.8
840HO	4000K	6000	89.3	67.2	101.4	59.2	80.6	74.4
840VHO	4000K	8000	87.7	91.2	100.0	80.0	78.1	102.4

90 CRI

927	2700K	4000	74.6	53.6	82.0	48.8	67.6	59.2
927HO	2700K	6000	73.5	81.6	80.6	74.4	66.4	90.4
930	3000K	4000	75.8	52.8	84.7	47.2	69.4	57.6
930HO	3000K	6000	75.8	79.2	83.3	72.0	68.2	88.0
935	3500K	4000	78.1	51.2	87.7	45.6	70.4	56.8
935HO	3500K	6000	77.3	77.6	85.2	70.4	70.1	85.6
940	4000K	4000	76.9	52.0	86.2	46.4	70.4	56.8
940HO	4000K	6000	77.3	77.6	85.2	70.4	69.4	86.4

Indirect 80 CRI

	Color	Lumens	HE		HEA	
			High Efficiency		Ascent	
			LPW	Watts	LPW	Watts
830	3000K	4000	122.0	32.8	119.0	33.6
830HO	3000K	6000	121.0	49.6	117.2	51.2
830VHO	3000K	8000	119.0	67.2	114.9	69.6
835	3500K	4000	125.0	32.0	119.0	33.6
835HO	3500K	6000	123.0	48.8	121.0	49.6
835VHO	3500K	8000	122.0	65.6	117.6	68.0
840	4000K	4000	125.0	32.0	128.2	31.2
840HO	4000K	6000	125.0	48.0	127.1	47.2
840VHO	4000K	8000	123.5	64.8	126.6	63.2



Output - Continued



Indirect 90 CRI

			HE		HEA	
			High Efficiency	Ascent	LPW	Watts
927	2700K	6000	102.0	39.2	100.0	40.0
927HO	2700K	9000	101.4	59.2	98.7	60.8
927VHO	2700K	12000	102.0	78.4	98.0	81.6
930	3000K	6000	106.4	37.6	104.2	38.4
930HO	3000K	9000	105.6	56.8	101.4	59.2
930VHO	3000K	12000	105.3	76.0	102.0	78.4
935	3500K	6000	108.7	36.8	106.4	37.6
935HO	3500K	9000	107.1	56.0	104.2	57.6
935VHO	3500K	12000	104.2	76.8	104.2	76.8
940	4000K	6000	108.7	36.8	104.2	38.4
940HO	4000K	9000	105.6	56.8	104.2	57.6
940VHO	4000K	12000	106.4	75.2	103.1	77.6

Mounting


- Aircraft cables mount directly to a standard junctionbox or structure
- Canopies, hubs, and pendants match fixture finish, power cords are white, grey, or black depending on fixture finish. See Finish section for additional details
- AH4 canopies can be installed below the ceiling plane or semi-recessed into the ceiling for a flush mount installation, no specification required (see below)
- Must specify cable length, either 48" or 120" standard, field adjustable
- Designed to install into acoustical grid and inaccessible ceilings
- Tie off fixture to structure with retention wires
- Maximum fixture weight is 35.8 lbs

AS4_JB 4 AC cables to fixture to J-Box	AH4_JB 4 AC cables with hub to fixture to J-Box
AS4_ST 4 AC cables to fixture to Structure	AH4_ST 4 AC cables with hub to fixture to Structure

AH4 Canopy Options

- The canopy can be installed either below the ceiling plane or semi-recessed into the ceiling for a flush mount installation
- Standard kit can be installed either way
- Flush canopy installation is not available for fixtures installed below a grid rail



Voltage

- Some QIVI configurations will not accommodate all voltage options; consult with factory

U	Universal
1	120 volt
2	277 volt
3	347 volt

Driver

- Standard Driver Option = OL2
- Driver Lifetime: 50,000 hours at 25°C ambient operating conditions
- Some QIVI configurations will not accommodate all driver options; consult with factory

OL2	Osram Optotronic 1%, 0-10v, nominal 1% dimming range
OL3	Osram Optotronic 347v 10%, 0-10v, requires 347v option
EE1	eldoLED ECOdrive 1%, 0-10v Logarithmic
EE2	eldoLED ECOdrive 1%, 0-10v Linear
ES1	eldoLED SOLOdrive 0%, 0-10v Logarithmic
ES2	eldoLED SOLOdrive 0%, 0-10v Linear
LH1	Lutron Hi-lume Soft-on, Fade-to-black 1%, EcoSystem, LDE1
L51	Lutron 5-Series 5%, EcoSystem, LDE5
PL2	Advance Xitanium 1%, 0-10v
PS1	Advance Xitanium Step Dimming 50%/100%
ND	Non-Dimming

Specifications and dimensions subject to change without notice. Specification sheets that appear on pinnacle-ltg.com are the most recent version and supersede all other previously printed or electronic versions.

Designed in Denver, CO • USA | pinnacle-ltg.com | O: 303-322-5570 F: 303-322-5568

Q3S-22DI_LED_SPEC_DEC2020



Circuiting

- Select fixture circuiting from options below
- Some QIVI configurations will not accommodate all circuiting options; consult with factory

1	Single Circuit
2	Dual Circuit
E	Emergency Circuit only
N	Night Light Circuit only

Battery

- Select battery section type if required, indicate total QTY. *Example 2P*
- 90 minute battery runtime; test button is remote to fixture and requires an additional drop
- For more battery options available, see Pinnacle Resource Guide

0	No battery
_P	Bodine 10w Integral
_I	Iota 10w Integral
_IC	Iota 10w Integral (CEC Listed)

For Approximate Battery Lumen Output

- Multiply battery wattage X fixture LPW shown on Lumen Table
- 92.3 (LPW) x 10 (watts) = 923 battery lumen output

Battery OR Emergency Ordering Examples

- Single circuit, 10w Integral Battery Ordering Code: 1-1P
- Emergency only, 10w Integral Battery Ordering Code: E-1P

Finish

- Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes
- Selecting a fixture finish other than white may impact lumen output; consult factory for more information

W	White (<i>white cord/white canopy</i>)
S	Metallic Silver (<i>grey cord/silver canopy</i>)
BL	Textured Black (<i>black cord/black canopy</i>)
BR	Bronze (<i>white cord/bronze canopy</i>)
GR	Graphite (<i>white cord/graphite canopy</i>)
CC	Custom Color (<i>white cord/color match canopy</i>)

Fixture Options

- Additional options to enhance the fixture and finish of the product

AM	Antimicrobial Paint
GMF	Internal Slow Blow Fuse
CC-C	Custom Color Canopy

Controls


- Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.



Photometrics

High Efficiency Lens

Test #	PRELIMINARY
Catalog #	Q3S-22DI-840-840
Lumens	8000 lm
Watts	70.4 W
Efficacy	114 LPW



PRELIMINARY

Approvals & Certifications

Construction: 6063-T6 Extruded aluminum housing. Highly reflective steel white painted reflector.

Shielding: Diffuse snap-in acrylic lens, removable for maintenance.

Mounting: Designed to install into acoustical grid and inaccessible ceilings. Tie off fixture to structure with retention wires. Maximum fixture weight is 35.8 lbs

LED: 25°C test environment. Lumen output/wattage has a margin of +/- 5%. All luminaire configurations tested in accordance with IES LM-79. Diodes tested in accordance with IES LM-80. Lifetime calculated using IES TM-21. Minimum lifetime greater than 60,000 hours. L70 = 136,200 hours and L90 = 41,100 hours. MacAdam 3-Step Ellipses. Not all products are Lighting Facts listed. For all available IES files, please visit our website at pinnacle-ltg.com.

CRI, CCT & Output: Two lumen packages available. Standard and High (HO). Custom outputs are available. Specify custom lumens or watts between standard offering listed on CRI, CCT & Output page. 80 CRI is available for 3000K, 3500K, and 4000K. 90 CRI is available for 2700K, 3000K, 3500K, and 4000K. 80 CRI = R9≥19 and 90 CRI = R9≥61.

Voltage: Universal (U), 120 volt (1), 277 volt (2) and 347 volt (3) options available. Must specify OL3 in Driver section when 347 volt (3) is selected. Some QIVI configurations will not accommodate all voltage options; consult with factory.

Driver: Standard Driver Option is Osram 0-10V, 1% = OL2. Electronic driver, Power factor is >0.9 with a THD <20%. Driver Lifetime: 50,000 hours at 25°C ambient operating conditions. Ambient operating range: -20°F/-30°C to 95°F/35°C. Some QIVI configurations will not accommodate all driver options.

Circuiting: Select from single circuit (1), Emergency circuit (E) or Night Light circuit (N). For emergency circuiting situations that require no through wire or circuit separation, Life Safety Circuit should be selected. This will provide a separate power feed and only the Life Safety Circuit in that section. Some QIVI configurations will not accommodate all circuiting options, consult with factory.

Finish: Standard powder-coat textured white, metallic silver, textured black, graphite or bronze painted finish; consult factory for chip of standard paint finishes. Canopies painted white unless specified differently in the options section of the part number. Contact factory for additional custom color and finish options.

Controls: Pinnacle is able to accommodate different control solutions from different manufacturers. Consult Factory for more information.

Labels: UL and cUL Listed. STD, HO and VHO lumen packages are approved for dry/damp location unless otherwise noted.

Fixture Weight: Maximum fixture weight is 35.8 lbs.

Buy American Act Compliant

Warranty: QIVI offered with a 5-year limited warranty. Covers LED, driver and fixture.