


PROJECT:	TYPE:	CAT. #:	SS -	- SMA -	-	-	-
----------	-------	---------	------	---------	---	---	---


PROFILE

LIGHT SOURCE	HIGH PERFORMANCE CC LED'S
OUTPUT	8.2 W (4.1 W DIRECT/4.1 W INDIRECT)
DISTRIBUTION	DIRECT/INDIRECT WITH OPTIONAL AMBIENT
CCT	2700K - 4000K
CRI	82 CRI
VOLTAGE	UNIVERSAL 120-277V
POWER	REMOTE POWER SUPPLY
CONTROL	0-10V, LUTRON HI-LUME PREMIER 0.1% ECOSYSTEM W/SOFT ON, FADE TO BLACK
SIZES	12", 24", 36" (NOMINAL)
HOUSING	MACHINED ALUMINUM
MOUNTING	SURFACE
GEM	ALUMINUM, BRASS, OR GLASS
FINISH	SILVER ANODIZED, WHITE OR BLACK, CC
WARRANTY	5-YEAR LIMITED
CERTIFICATION	ETL AND cETL FOR DRY LOCATION



FIXTURE SHOWN: SS-40K-SMA-XX-DIM-TB-AWL


DISTRIBUTION



GEMS



PROFILE



FINISHES



PROJECT:	TYPE:	CAT. #:	SS -	- SMA -	-	-	-	-
----------	-------	---------	------	---------	---	---	---	---

SPECIFICATION

SS		SMA					separate options with dashes
----	--	-----	--	--	--	--	------------------------------

1	2	3	4	5	6	7
---	---	---	---	---	---	---

1 FIXTURE

SCOPE SCONCE	SS
--------------	----

2 CCT

2700K	27K
3000K	30K
3500K	35K
4000K	40K

3 MOUNTING

SURFACE MOUNT ARCH.	SMA
---------------------	-----

4 SIZE

11.38"	12
23.38"	24
35.38"	36

5 CONTROL

0-10V DIMMING	DIM
one power supply provided for each fixture	
LUTRON	PEQ
Hi-lume Premier 0.1% EcoSystem w/Soft On, Fade to Black	
one power supply provided for every two fixtures	
dimming control system to be supplied by others	

6 LUMINAIRE FINISH

SILVER ANODIZED	AL
brushed and silver anodized housing components	
TEXTURED WHITE	TW
TEXTURED BLACK	TBL
TEXTURED GREY	TG
CUSTOM COLOR	CC
selected finish is used for all parts of the fixture unless an alternative gem option is selected	
contact factory for custom color additional charges will apply	

7 OPTIONS

AMBIENT WHITE LIGHT	AWL
a polished crystal gem that has a soft ambient glow ambient glow is same CCT as previously selected	
SILVER ANODIZED GEM	BA
machined aluminum with brushed and silver anodized finish	
not available with ambient glow	
BRUSHED BRASS GEM	BB
machined brass with brushed finish	
brass is a natural metal and will patina over time	
not available with ambient glow	
JBOX MOUNTING KIT	JBK
cover plate to allow mounting to a single gang junction box	

PROJECT:	TYPE:	CAT. #:	SS -	- SMA -	-	-	-
----------	-------	---------	------	---------	---	---	---

PERFORMANCE

TEST DATA USING 3000K WHITE LIGHT SOURCES

GEM TYPE	TOTAL WATTAGE	DELIVERED LUMENS	LUMINAIRE EFFICACY	PEAK CANDELA
GLASS (AWL)	8.2 W	540 LM	66 LM/W	201
BRUSHED BRASS (BB)	8.2 W	406 LM	50 LM/W	176
SILVER ANODIZED (BA)	8.2 W	452 LM	45 LM/W	172
TEXTURED WHITE	8.2 W	414 LM	51 LM/W	179
TEXTURED BLACK	8.2 W	268 LM	32 LM/W	162

FIXTURES PER 15A CIRCUIT (AT FULL LOAD)

	120V	277V
SINGLE FIXTURE	176	400

POWER SUPPLIES PER 15A CIRCUIT (AT FULL LOAD)

	CONTRA 0.5 (96.0 W)	LUTRON (20.0 W)
120V	15	30
277V	30	60


REMOTE DISTANCE LIMITS

WIRE GAUGE	MAX DISTANCE	NOTE: NON-COMPLIANCE WITH RECOMMENDED REMOTE WIRING DISTANCES MAY VOID WARRANTY
22 AWG	25.0 FT	
20 AWG	40.0 FT	
18 AWG	60.0 FT	
16 AWG	100.0 FT	
14 AWG	150.0 FT	
12 AWG	200.0 FT	


PROJECT:	TYPE:	CAT. #:	SS -	- SMA -	-	-	-
----------	-------	---------	------	---------	---	---	---

DIMENSIONS

SURFACE MOUNT ARCHITECTURAL (SMA)




SURFACE MOUNT ARCHITECTURAL WITH OPTIONAL JBOX COVER PLATE (SMA + JBK)




PROJECT:	TYPE:	CAT. #:	SS -	- SMA -	-	-	-
----------	-------	---------	------	---------	---	---	---

SMA - SURFACE MOUNT ARCHITECTURAL




A low-profile back block that mounts directly to a wall to provide a clean and minimal look. For this configuration power supply must be installed remotely in a junction box or similar rated enclosure, and all splicing at fixture must be done in accordance with electrical code.

JBK - JBOX MOUNTING KIT (OPTIONAL)



Optional cover plate provided allow mounting to single gang junction boxes at power feed location. Power supply to install in single gang junction box. Junction box provided by others. Cover plate finish same as fixture.

LUTRON (PEQ) - REMOTE POWER SUPPLY




Remote power supply enclosure. 20.0 W Hi-lume Premier 0.1% EcoSystem w/Soft On, Fade to Black. One power supply provided with every two fixtures.


PROJECT:	TYPE:	CAT. #:	SS -	- SMA -	-	-	-
----------	-------	---------	------	---------	---	---	---

WIRING EXAMPLES


SURFACE MOUNT ARCHITECTURAL (SMA)



JBOX MOUNTING KIT (JBK)



LUTRON REMOTE POWER SUPPLY & JBOX MOUNTING KIT (LDE1 & JBK)



ONE POWER SUPPLY PROVIDED FOR EVERY TWO FIXTURES