

# LIMBURG Collection

## Pendant luminaire with three-ply opal glass

**Material:** Luminaire housing and canopy constructed of aluminum with painted white or chrome finish. White luminaire provided with white connecting cable, chrom luminaire provided with black connecting cable. Designed for attachment to ceiling over standard 4" octagonal wiring box (by others).

**Glass:** Hand-blown, three-ply opal glass. Interior diffuser made of frosted acrylic.

**Electrical:** 22.8W LED luminaire, 26.4 total system watts, -20°C start temperature. 120V through 277V electronic LED driver located in ceiling canopy, 0-10V dimming. LED module(s) are available from factory for easy replacement. LED color temperature is 3000K with a >80 CRI Available in 4000K (>80 CRI); add suffix K4 to order.

**Note:** LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to [www.bega-us.com](http://www.bega-us.com).

**Finish:** Select the desired material finish by using appropriate code number as suffix


- White Code number **.1**
- Chrome Code number **.3**

**CSA** certified to U.S. and Canadian standards, suitable for damp locations. Interior use only.

**Weight:** 7.1 lbs

**Luminaire lumens:** 2247 lumens

Type:  
 LIMBURG Product:  
 Project:  
 Voltage:  
 Color:  
 Options:  
 Modified:



Pendant luminaires					
	Finish	LED	A	B	L
<b>56 607.1</b>	White	22.8 W	6	13 <sup>3</sup> / <sub>4</sub>	81
<b>56 607.3</b>	Chrome	22.8 W	6	13 <sup>3</sup> / <sub>4</sub>	81