

Application

Recessed wall luminaire with shielded light distribution for glare-free illumination of ground surfaces, building entrances, stairs and pathways.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 Safety glass with optical texture
 Silicone applied robotically to casting, plasma treated for increased adhesion
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners
 Stainless steel screw clamps
 Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65
 Weight: 1.9lbs

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -40° C
 LED module wattage 4.0W
 System wattage 7.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 191 lumens (4000K)
 LED service life (L70) 50,000 hours

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors Black (BLK) White (WHT) RAL:
 Bronze (BRZ) Silver (SLV) CUS :



Recessed wall luminaire · shielded

	LED	A	B	C
24 151 ADA	4.0 W	5 1/8	5 1/2	3/4

Type:
 BEGA Product:
 Project:
 Modified:

