

**Application**

Recessed wall luminaire with shielded light distribution for glare-free illumination of ground surfaces, building entrances, stairs and pathways.

**Materials**

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 Safety glass with optical texture  
 Silicone applied robotically to casting, plasma treated for increased adhesion  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners  
 Stainless steel screw clamps  
 Composite installation housing

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65  
 Weight: 3.3lbs

**Electrical**

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	7.7 W
System wattage	11.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	565 lumens (4000K)
LED service life (L70)	50,000 hours

**LED color temperature**


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



**Recessed wall luminaire · shielded**

	LED	A	B	C
<b>24 152</b> <b>ADA</b>	7.7 W	7 3/8	5 1/2	1 1/4

Type:  
 BEGA Product:  
 Project:  
 Modified:

