

Application

Recessed wall luminaire with directed light distribution for the illumination of ground surfaces, stairs and pathways.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Safety glass with optical texture
 Silicone applied robotically to casting, plasma treated for increased adhesion
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners
 Stainless steel screw clamps
 Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65
 Weight: 2.2lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-40° C
LED module wattage	2.9W
System wattage	5.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	410 lumens (4000K)
LED service life (L70)	50,000 hours

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



Recessed wall luminaire · directed light

	LED	A	B	C
24 206 ADA	2.9 W	5 7/8	5 7/8	5 1/4

Type:
 BEGA Product:
 Project:
 Modified:

