

#### Manufactured in the USA - IBEW

PRODUCT LISTED BY A NATIONALLY RECOGNIZED TESTING


### **Features**


- Accepts short neck PAR30 lamps and LEDs
- Available in 1 to 5-light linear, square and corner configurations
- Blends into the ceiling and can be installed with or without trim
- Each lamp is individually mounted for pan and tilt.
- Lamp holders accept a variety of lenses and accessories
- Easy front re-lamping
- Thermal protector
- Adjustable trim with torsion springs for ceilings up to 2" thick
- Adjustable butterfly mounting brackets included
- Fully enclosed wiring compartment
- Black, white and silver trims available custom colors upon request
- 120-volt

# **30R PAR30**Specification Sheet - New Construction



5 Holt Drive, Stony Point, NY 10980 845-947-3034 info@tslight.com





	Length	Width	Height	Ceiling Cut-Out	
Model #	(A)	(B)	(C)	(D)	(E)
30R-1	14¾"	8¾"	9¼"	7 1/16"	8"
30R-2	20¼"	8¾"	9¼"	7 1/16"	13%"
30R-3	26%"	8¾"	9¼"	7 1/16"	19%"
30R-4	32%"	8¾"	9¼"	7 1/16"	25¾"
30R-4S	19¼"	16½"	7%"	12%"	13¾"
30R-3L	19%"	19%"	7%"	6¼" x 13%"	13%" x 6%"
30R-5L	25%"	25%"	7%"	6¼" × 19¾"	19¾" × 6¼"

## **Ordering Matrix**

Model	# of Lamps	Voltage	Inside Finish	Trim Finish
30R	1 = 1-Linear 2 = 2-Linear 3 = 3-Linear 4 = 4-Linear 4S = 4-Square 3L = 3-Corner 5L = 5-Corner	120 = 120V	B = Black W = White S = Silver CC = Custom	B = Black W = White S = Silver CC = Custom

Maximum Ambient temperature: 35°C

**Example:** 30R-3-B-W-120

30R-\_\_\_\_-

## **1-Linear** 30R-1



**2-Linear** 30R-2



**3-Linear** 30R-3



**4-Linear** 30R-4



**NOTE:** These fixtures are not IC or Chicago Plenum Rated.

## **Accessories**

 GF40
 Colored Glass

 GF40-601
 Beam Softener

 GF40-600
 5°x50° Linear

 GF40-673
 50°x50° Spread

 GF40-702
 UV Blocking

 HD40
 Snoot

 XH40
 Cross Baffle

## **4-Square** 30R-4S





**5-Corner** 30R-5L

