

# ASPIRE CW IP



5 Holt Drive,  
Stony Point, NY 10980  
845-947-3034  
info@tslight.com

The IP65 rated ASPIRE CW IP™ ellipsoidal features a High Power 130W Cool White >90CRI 5,600K LED engine producing 11,000+ total lumens, 19°, 26°, 36°, and 50° interchangeable lens options (sold separately), (4) blade manual framing shutters, supports B size metal gobos (2 sample gobos included, single gobo holder not included) and an optional IP65 rated DMX controlled dual gobo rotator (sold separately), manual focus, DMX controlled electronic strobe, 16bit dimming and selectable dimming curve modes, flicker free operation for TV and FILM, adjustable refresh frequency and gamma brightness, IP rated 5pin DMX and powerCON TRUE1 in/out connections, (4) button LCD control display panel, an integrated rigging yoke, quiet fan cooling, and a multi-voltage universal auto switching power supply (100-240v).

## Features

- IP65 Rated High Power 130W Cool White 5,600K LED Engine
- >90CRI and 11,000+ Total Lumens Output
- Interchangeable Lens Options\* 19°, 26°, 36°, 50°
- Supports B Size Metal Gobos\*\*
- IP65 DMX Controlled Dual Gobo Rotator\*
- (4) Blade Manual Framing Shutters
- DMX Controlled Electronic Strobe and 16bit Dimming
- Selectable Dimming Curve Modes
- Flicker Free Operation for TV and FILM
- Adjustable Refresh Frequency and Gamma Brightness
- Quiet Fan Cooling
- (\*sold separately) (\*\*2 sample gobos included, holder not included)

## Optional Accessories

- PHD019** Profile High Definition Lens 19°
- PHD126** Profile High Definition Lens 26°
- PHD236** Profile High Definition Lens 36°
- PHD350** Profile High Definition Lens 50°

## Source

- High Power 130W Cool White LED Engine
- 50,000 Hour Average LED Life\*
- \*LED Life may vary depending on several factors including but not limited to:  
  
Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

## Photometric Data

- > 91CRI | 11,000+ Total Lumens

## Gobos

- Supports "B" Size Metal Gobos\*\*
- IP65 Rated DMX Controlled Dual Gobo Rotator\*\*\*
- \*\*Gobos and Holder not included.  
\*\*\*Rotator Sold Separately

## Size / Weight

- Length: 29.6"
- Width: 13.9"
- Vertical Height: 18.9"
- Weight: 24 lbs.

## APPROVALS / RATINGS

- CE
- cETLus
- IP65

## Effects

- Electronic Strobe and 16bit Dimming
- Selectable Dimming Curve Modes

## Controls / Connections

- 3 DMX Channel Modes (3 / 6 / 8)
- Adjustable Refresh Rates
- Adjustable Gamma Brightness
- 4 Button Control Panel / LED Menu Display
- IP Rated 5pin DMX In/Out / powerCON TRUE1 In/Ou

## Electrical / Thermal

- Quiet Fan Cooling
- AC 100-240V - 50/60Hz
- 170W Max Power Consumption
- 14° to 113°F (-10° to 45°C)

**19° LENS ZOOM IN @ FULL ON | 5,708K**

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
3,788	606	309	152	67	38

**19° LENS ZOOM OUT @ FULL ON | 5,695K**

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
3,403	544	278	136	60	34

**26° LENS ZOOM IN @ FULL ON | 5,648K**

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
2,910	466	238	116	52	29

**26° LENS ZOOM OUT @ FULL ON | 5,703K**

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
2,663	426	217	107	47	27

**36° LENS ZOOM IN @ FULL ON | 5,713K**

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
1,621	379	167	97	46	29

**36° LENS ZOOM OUT @ FULL ON | 5,720K**

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
1,621	379	167	97	46	29

**50° LENS ZOOM IN @ FULL ON | 5,675K**

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
1,621	379	167	97	46	29

**50° LENS ZOOM OUT @ FULL ON | 5,686K**

6.6 ft	16.4 ft	23 ft	32.8 ft	49.2 ft	65.6 ft
fc	fc	fc	fc	fc	fc
1,621	379	167	97	46	29

For standard and custom patterns please see the pattern specification sheet. For a complete list, please contact a Times Square Lighting representative.

View Patterns: <http://tsq.li/2bMBz3l>

