P38SK PAR38




BY A NATIONALLY RECOGNIZED TESTING LABORATORY



The P38SK's size makes this unit ideal for short to medium throw lighting in galleries, museums, retail and residential applications. Equipped with a self-locking yoke and accessory-retaining clips that accepts louvers, barndoors, hoods and filters. Available in standard black, white and silver finishes. Custom colors are available by request and at an additional charge.

FEATURES

- Accepts PAR38 lamps and LED's
- Numerous mounting options and accessories
- Weight: 1 lbs



MODEL NUMBER	FINISH	MOUNTING	ACCESSORIES
P38SK	B Black W White S Silver CC Custom Color	AD1 Track Adapter. 1 or 2 Circuit track. 120V. TA1 Track Adapter. E-Series. 1 Circuit. 120V. TA2 Track Adapter. G-Series. 2 Circuit. 120V. TA3 Track Adapter. G-Series. 3 Circuit. 120V.	LV7 Louver XL7 Cross Baffle Louver BD7 Barndoor HD7 Hood XH7 Cross Baffle Hood
		CM4 Canopy Mount.	CF7 Color Frame GF7 Glass Color Filter GF7-600 5°x50° Linear Lens GF7-601 Beam Softener GF7-673 50°x50° Spread Lens CC18 Coiled Cord SC-24 Safety Cable
		US1 6 5/8" x 1 1/2" Unistrut Adapter.	
		TB4 6 1/4" Portable Wall Mount/Table Base Floor.	
		MC Light Duty Pipe Clamp. For pipes up to 15/16" O.D. MN Medium Duty Pipe Clamp. For pipes up to 2" O.D.	

EXAMPLE: P38SK - B - TA2 - LV7

MODEL NUMBER	FINISH	MOUNTING	ACCESSORIES
P38SK			