

Construction

- Made of Polyvinyl chloride
- Weight: 13.2 lbs

Accessories

400TH Snoot 400HH Half Snoot 400CF Color Frame 400PH-B-V Steel Pattern Holder 400PH-G Glass Pattern Holder 400DN Pattern Donut **400RS** Drop-In Iris Pattern Rotator-Dual **SmartMove**

Mounting Options

US1 Unistrut adapter.

PC9M Heavy duty pipe clamp for large, heavy fixtures. For pipes 1/2" to 11/2" O.D.

CM4 6" Canopy for permanent mounting on standard 4" octagonal outlet boxes.

TB8 8" x 8" Portable table base for floor or table use.

SC 1/8" diameter, 30" long steel safety cable with snap ring. Used as added security when large or heavy fixtures are being used.

Valiant Series

200W White & RGBW LED



The Valiant Series from Times Square Lighting is a range of LED Ellipsoidals. This series features high quality optics, high CRI, and is available in 200W white and RGBW models. The unit is capable of sharp pattern projection and comes equipped with framing shutters. Patterns can be standard or custom metal gobos, or even plastic slides thanks to the unit's cool-running nature.

5 Holt Drive, Stony Point, NY 10980 845-947-3034 info@tslight.com

The Valiant Series accepts DMX-512 input for color and strobe function control. A DMX output is provided on the unit as well.

The Valiant Series is available with 19°, 26°, 36°, and 50° interchangeable lens tubes. The fixture is made from high-grade PVC and is available in black finish.

LED

- 200W Nichia LED available in White and RGBW
- CRI = 90
- LED life rated for over 50,000 hours
- 3000K Color Temperture for warm white ellipsoidal

DMX

- DMX-512 Control
- Master/Slave Function
- Dimming from 0 ~ 100%
- Strobe from 1 to 25 times per second
- Autorun mode

Optics

- Lens tube options of 19°, 26°, 36° and 50°
- Adjustable Focus
- High Quality Optics with glass reflector

Color Rendering

Ra	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15	Re
90	90	94	97	89	88	92	92	80	54	85	87	75	91	98	86	87

Ordering Matrix


Model	Lens Tube	Connector (Optional)	Mounting	Accessories
V200 = White V200C = RGBW	419L=19° 426L = 26° 436L = 36° 450L=50°	E2867 = Edison Plug E876 = Twist Lock 600G = Stage Pin	See Mounting Options	See Accessory Options


Example: V200-419L-E2867-US1-400TH


V200-____-__-


Photometrics

19° Setting Distance Beam Spread Footcandles 5 ft 1.6 ft 3370 10 ft 3.2 ft 842 15 ft 4.8 ft 374 20 ft 6.4 ft 211










Wiring Details





XLR 5FEM

XLR 5MALE

Patterns

For standard and custom patterns please see the pattern specification sheet.





Click here to download pattern datasheet.