


VT03 | Surface Mount / Pendant Extrusion



The VT03 is a medium size extrusion constructed from high quality anodized aluminum that can be suspended as contemporary pendant light, or surface mounted for a sophisticated modern light fixture. The VT03 is accessorized with low-profile mounting hardware; when paired with the VT03-SL, a satined polycarbonate diffusor, creates a cylindrical look.



Product Detail:

Material:	Extruded Aluminum
Color:	Anodized Silver
Size in inch:	L $78 \frac{3}{4}$ x W $1 \frac{37}{64}$ x H $\frac{25}{64}$
Customization:	Cut to specified length

Applications:

- Pendant
- Surface Mount
- Hallways
- Wall Sconces
- Vanity
- Office
- Retail

Compatible Lens

VT03-SL
Satined Lens



Compatible LED Tapelight

Product	Output (~lm/ft)	LEDs/ft	Consump. (watt/ft)	Efficacy (~lm/watt)	CRI	Voltage	Max Run Length	Cut Increment
---------	-----------------	---------	--------------------	---------------------	-----	---------	----------------	---------------

Vienna (High End)

L90	90	36	0.73	123	>80	24	75'	2"
L180	180	36	1.62	111	>80	24	47'	2"
L270	270	36	2.7	108	>80	24	34'	2"
L400	400	36	3.9	109	>80	24	25'	2"
L610	610	36	6.2	104	>80	24	18'	2"
L910	910	36	9.7	104	>80	24	10'	2"
RGB	Max 110	18	2.2	N/A	N/A	24	20'	4"
Tunable White	460	72	4.12	111	>80	24	30'	2"

Florence (Mid-Range)

L200	200	36	1.6	125	>90	24	55'	2"
L360	360	36	2.9	124	>90	24	42'	2"
L500	500	36	4.3	116	>90	24	32'	2"
L780	780	36	6.9	113	>90	24	24'	2"
L990	990	36	9.2	108	>90	24	16'	2"
RGB	200	36	7.3	29	N/A	24	16'	2"
RGBW	330	29	7.3	47	N/A	24	16'	2.5"
Tunable White	590	73	5.9	100	>90	24	16'	2"

Athens (Economy)

L240	240	36	2.1	117	>90	24	26'	2"
L460	460	36	4.1	114	>90	24	16'	2"
L680	680	36	6.3	109	>90	24	13'	2"

Paris (MegaCRI 95+)

L500	564	36	6.1	92	>95	24	16'	2"
------	-----	----	-----	----	-----	----	-----	----

Madrid (120V)

L360	360	22	4	90	>80	120	164'	4"
------	-----	----	---	----	-----	-----	------	----

VT03 | Surface Mount / Pendant Extrusion



Ordering Code Template: VT03 + Tapelight + Accessories

Extrusion	Lens	TL Line	Lumen Output	IP	CCT	End Cap	Mounting
-----------	------	---------	--------------	----	-----	---------	----------


Ordering Code: VT03 + Tapelight + Accessories

VT03	- SL	- F	- L200	IP00	CT35	- EC	- MP
------	------	-----	--------	------	------	------	------

Extrusion	Lens	Tapelight			End Cap	Mounting	
VT03	SL – Satined Lens	V – Vienna	L90 – 90 lm/ft L180 – 180 lm/ft L270 – 270 lm/ft L400 – 400 lm/ft L610 – 610 lm/ft L910 – 910 lm/ft RGB - RGB TW - Tunable White	IP00	CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K	EC – End Cap	MP – Mounting Plate LC – Linear Connector CS – Cable Suspension Kit
				IP66	CT27 - 2700K CT30 - 3000K CT40 - 4000K		
		F – Florence	L200 – 200 lm/ft L360 – 360 lm/ft L500 – 500 lm/ft L780 – 780 lm/ft L990 – 990 lm/ft RGB - RGB RGBW - RGBW TW - Tunable White	IP00 IP66	CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K		
				IP00 IP65	N/A		
		A – Athens	L240 – 240 lm/ft L460 – 460 lm/ft L680 – 680 lm/ft	IP00 IP66	CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K		
		P – Paris	L500 – 564 lm/ft	IP20	CT24 - 2400K CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K		
M – Madrid	L360 – 360 lm/ft	IP65	CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K				

Accessories

VT03-EC



End Cap

ZZ99-MP



Mounting Plate

ZZ99-LC



Linear Connector

ZZ99-CS



Cable Suspension
Kit

Customization	LN20-CUST	EX20-CUST	M20-CUST	E20-CUST	E20-CUST-C
Cutting lens to specified length	✓				
Cutting extrusion to specified length		✓			
Miter corner extrusion and diffuser			✓		
Cutting extrusion, diffuser, and tapelight				✓	✓
Cutting extrusion, diffuser, and tapelight to 1-2 ft					
Cutting extrusion, diffuser, and tapelight to 3-4 ft					
Cutting extrusion, diffuser, and tapelight to 5-6 ft					
Installing the tapelight into the extrusion				✓	✓
Adding strain relief and power feed				✓	✓
Adding strain relief and power feed w/ heat sink tube					
Mounting end caps				✓	✓
Mounting and sealing end caps					
Customize to specified color					✓
Solder 4 ft lead wire				✓	✓
Filling extrusion w/ clear material => 2 ft submersible					
Final function and quality inspection	✓	✓	✓	✓	✓

Power Supply Ordering Code

TR + 50 + IP00 = Non-Dimming, 50 watt, IP00, 88-264V output, 24V

1 - Model	2 - Power	3 - IP	Input	Output	Dimension (Inch) LxWxH
TR = Non-Dimming	50 = 50 watt 75 = 75 watt 100 = 100 watt 150 = 150 watt	IP00 = Indoor	88-264V	24V	3.90 X 3.82 X 1.42 5.08 X 3.82 X 1.50 6.26 X 3.82 X 1.50 7.84 X 3.85 X 1.50
	12 = 12 watt 16 = 16 watt 25 = 25 watt 35 = 35 watt	IP42 = Indoor	90-264V		3.03 X 1.57 X 1.14 3.03 X 1.57 X 1.14 3.31 X 2.24 X 1.16 3.31 X 2.24 X 1.16
	20 = 20 watt 35 = 35 watt 60 = 60 watt 100 = 100 watt	IP67 = Outdoor	90-264V		4.65 X 1.38 X 1.02 5.83 X 1.57 X 1.18 6.40 X 1.67 X 1.26 7.48 X 2.05 X 1.46
DTR = Dimming (0-10V)	16 = 16 watt 25 = 25 watt 40 = 40 watt 60 = 60 watt 90 = 90 watt 100 = 100 watt 120 = 120 watt 150 = 150 watt 185 = 185 watt 240 = 240 watt 320 = 320 watt 600 = 600 watt	IP67 = Outdoor	90-305V	24V	5.83 X 1.57 X 1.26 5.83 X 1.57 X 1.26 6.40 X 1.70 X 1.26 6.40 X 1.70 X 1.26 6.34 X 2.40 X 1.42 8.66 X 2.68 X 1.53 8.66 X 2.68 X 1.53 8.97 X 2.68 X 1.58 8.97 X 2.68 X 1.58 9.88 X 2.68 X 1.58 9.92 X 3.54 X 1.72 11.02 X 5.67 X 1.91
DTR – FP = Dimming (Forward Phase)	20 = 20 watt 40 = 40 watt 60 = 60 watt 75 = 75 watt 96 = 96 watt	IP67 = Outdoor	120V	24V	4.92 X 1.97 X 0.77 4.92 X 1.97 X 0.77 4.92 X 1.97 X 0.77 4.92 X 1.97 X 0.77 4.92 X 1.97 X 0.77